SAFETY DATA SHEET

NADREIN Coating



Section 1. Identification

Product identifier : NADREIN Coating Part A

Product type : Liquid

Product use : Hi-performance Coating
Supplier : PodLee International LTD.

ADD : 7400 S Miller Rd, Buckeye, AZ 85326, USA

EMERGENCY TELEPHONE NUMBER : +1 213 9868879

Section 2. Composition/information on ingredients

PART A

 Ingredient name
 : CAS number
 %

 Titanium dioxide
 : 7440-66-6
 18-25

 Hydroxy polyester
 : 27-36

 Barium sulfate
 : 13462-86-7
 9-14

 Carbon black
 : 1333-86-4
 14-18

Section 3. Hazards identification

Classification of the substance or : Not classified

mixture

GHS label elements

Hazard pictograms :



Signal word : Warning.

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a physical hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

Precautionary statements

Prevention : Wear eye protection as required.

Wear full face-shield during thermal processing if contact with

molten material is possible.

Wash hands thoroughly after handling.

Response : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing. Seek immediate medical attention

IF SWALLOWED, Seek immediate medical attention.

Product Name: NADREIN Hi-performance Coating Page: 1 / 7

Version 2.01 Date of issue 10/18/2024 Language English

Storage: Not applicable.Disposal: Not applicable.Other hazards: Defatting to the skin.

Section 4. First aid measures

Skin contact : Rinse with plenty of water and soap. Remove and isolate

contaminated clothing and shoes. Keep the patient warm. If you feel skin irritation or a rash, please get medical aid.

Eye contact : Wash immediately with plenty of water. After the initial

cleaning, remove the invisible eyes and continue cleaning for at least 15 minutes. Wash immediately with plenty of water. After the initial cleaning, remove the invisible eyes and

continue cleaning for at least 15 minutes.

Inhalation: If remove to fresh air. Seek medical attention if cough or other

symptoms develop or persist.

Ingestion : Normally not needed, if large quantities are ingested or if you

feel unwell, please get medical attention.

Most important symptoms and : At processing temperatures, the combined ingredients

effects, both acute and delayed (elastomer and other processing ingredients) may emit fumes

and vapors that may cause irritation to the eyes. Processing operations may create vapors or fumes which may cause

respiratory tract irritation.

Section 5. Firefighting measures

Hazardous Combustion Products : Heating decomposition products flammable gas.

Suitable extinguishing Media : Fog water, foam, dry powder

Extinguishing media to avoid : Use extinguishing media suitable for Class A fires (ordinary

combustibles). Carbon dioxide is generally not recommended for use on Class A fires as a lack of cooling capacity may

result in reignition.

Specific Hazards : Special precautions must be taken if this product is ground or

otherwise formed into a fine powder or dust since many organic substances in these forms present a dust explosion hazard. Dust in sufficient quantities may be ignited in air. Minimize dust generation and accumulation. Minimize activities which will float or suspend particles in air. Protect

from sources of ignition.

Toxic gases may be formed upon combustion and represent a

hazard to firefighters.

Special fire fighting : Wear fire-resistant clothing and air respirators in restricted

spaces.

Protection of fire-fighters : Firefighters must use standard protective equipment including

flame retardant coat, helmet, gloves, rubber boots, and SCBA.

Product Name: NADREIN Hi-performance Coating Page: 2 / 7

Version 2.01 Date of issue 10/18/2024 Language English

Section 6. Accidental release measures

Avoid contact with spilled or released materials. For guidance on the selection of personal protective equipment, see Chapter 8 of the safety data sheet. Please refer to Chapter 13 for disposal information. Please comply with all applicable local and international regulations.

Personal precautions

: Wear long sleeves and gloves to prevent skin contact. Launder contaminated clothing before reuse. Wash thoroughly after handling.

Clean-up methods and materials and containment measures

As with all industrial chemicals, use of good chemical hygiene and environmental stewardship practices recommended. Do not walk through spilled material. Clean up spills immediately. Do not flush spill to drain without permission from the appropriate authority.

Regulatory Requirements

: Follow applicable OSHA regulations (29CFR 1910.120).

Section 7. Handling and storage

Handling and Technical measures : and Safe handling advice

Product will emit fumes and vapors when heated to processing temperatures. Use only with adequate ventilation. Do not breathe (dust, vapor or fumes). Wash thoroughly after handling. Do not eat, drink or smoke in processing areas. Clean up following normal processing must be performed with adequate ventilation. Elastomer may be held at process temperatures for a short time without significant thermal degradation. However, exposure to elevated temperatures or excessive time will result in decomposition. Equipment should not be shut down for extended time periods with compound in it or decomposition may occur. Processing fume condensates, which may include toxic contaminants, may be combustible and should be periodically removed from exhaust hoods, duct work, and other surfaces. Protective clothing and gloves should be worn during cleanup operations to prevent skin contact. Combustible dust clouds may be created where operations produce dust.

Minimize dust generation and accumulation, especially on horizontal surfaces and duct work. Handling and processing operations should be conducted in accordance with NFPA-654 or similar best practices. Abnormal conditions such as equipment malfunction or using improper equipment or procedures, or hangup or stagnation of material during processing may cause composition. Employees involved in removing decomposing material should be provided suitable air supplied respirators, such as an approved positive pressure self-contained breathing apparatus. Compounding ingredients added to elastomer products may require special handling. It is

Product Name: NADREIN Hi-performance Coating
Version 2.01

Date of issue 10/18/2024

Page: 3 / 7

Language English

the user's responsibility to follow the recommended precautions of the individual additive suppliers.

Storage conditions Store indoors in a cool, ventilated and dry place. Keep away

> from heat source and kindling, and protect against freezing and rain, avoid sun exposure. Avoid contact with oxidants. The

container shall be grounded to prevent static electricity.

Storage temperature: 41°F/5 °C - 104°F/40 °C.

Storage period: 24 months.

Section 8. Exposure controls/personal protection

Maximum permissible No data available.

concentration

Monitoring method No data available. **Engineering measures** No data available.

Ventilation Provide good ventilation to ensure that the volatile gas content

in the indoor volume is below the allowable limit value.

Respiratory protection When the air concentration exceeds the standard, wear self-

> priming filter gas mask (half face), and wear air respirator or oxygen respirator during emergency rescue or evacuation.

Protective Clothing/Equipment

Wear penetrating work clothes.

Contaminated Equipment Separate contaminated work clothes from street clothes.

Launder before reuse. Remove this material from your shoes

and clean personal protective equipment.

Other protection Smoking, eating and drinking are strictly prohibited in the

workplace, bathing and changing clothes after work, regular

physical examination.

Section 9. Physical and chemical properties

Viscous liquid (color adjustable) **Appearance**

PH

Proportion Closed cup: >26°C (>79°F) [Cleveland ASTM D 93]

Boiling point, Initial boiling point

and boiling range

No data.

Relative density (water=1) No data. Relative vapor density (air =1) No data. Saturated vapor pressure (kPa) No data. No data. Heat of combustion (KJ/mol) No data. The critical temperature (°C) **Critical pressure (MPa)** No data.

Opposite value of octanol/water

No data.

distribution coefficient

Flash point No data. **Auto-ignition temperature** No data.

Product Name: NADREIN Hi-performance Coating Page: 4 / 7 Version 2.01 Date of issue 10/18/2024 Language English Explosive limit % (V/V) : No data.

Explosion threshold %(V/V) : No data.

Molecular formula : No data.

Molecular weight : No data.

Evaporation rate : No data.

Viscosity : No data.

Solubility : Not soluble in water.

Section 10. Stability and reactivity

Chemical stability : At room temperature and pressure.

Incompatible materials : No data.

Conditions to avoid : High temperature, open flame, incompatible materials,

Strong oxidant

Hazardous decomposition products: Carbon monoxide, Carbon dioxide.

Section 11. Toxicological information

Acute Toxicity : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Skin corrosion/irritation : No known significant effects or critical hazards.

Inhalation : Vapour inhalation under ambient conditions is not normally a

problem due to low vapour pressure.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : No known significant effects or critical hazards.

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following: irritation,

dryness, cracking

Ingestion : No specific data.

Section 12. Ecological information

Toxicity : No known significant effects or critical hazards.

Environmental effects

Persistence/degradability : Expected to be biodegradable.

Bioaccumulative potential : No specific data.

Other ecological information : No data.

Section 13. Disposal considerations

Disposal methods : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties

of the material generated to determine the proper waste classification and disposal methods in compliance with

Product Name: NADREIN Hi-performance Coating Page: 5 / 7

Version 2.01 Date of issue 10/18/2024 Language English

Local disposal regulations

applicable regulations. Do not dispose in drains or in water.

In accordance with the regulations currently in force and as far as possible, they should be disposed of by an approved waste

collector or contractor.

Disposal methods should comply with

local/regional/national/international regulations.

Section 14. Transport information

Land transport (as per

ADR/RID classification)

regulations.

Inland waterways transport

(ADN)

This substance is not classified as dangerous under ADN

This substance is not classified as dangerous under ADR/RID

regulations.

Sea transport (IMDG) : This substance is not classified as dangerous under IMDG

regulations.

Air transport (IATA) : This substance is not classified as dangerous under IATA

regulations.

DOT (US) This substance is not classified as dangerous under DOT

regulations.

Section 15. Regulatory information

Applicable regulations Chemical Hazardous Materials Safety Management Regulations

(promulgated by the State Council on February 17, 1987),

Chemical Hazardous Materials Safety management.

Regulations Implementation Rules (Chemical Labor Development [1992] 677), regulations on the safe use of

chemicals in the workplace ([1996] No. 423 of the Ministry of Labor Affairs) and other regulations, have made corresponding

regulations on the safe use, production, storage, transportation,

loading and unloading of chemical dangerous goods.

Chemical Weapon Convention

chemicals

List Schedules I, II & III

Montreal Protocol Not listed. Not listed. **Stockholm Convention on**

Persistent Organic Pollutants

Rotterdam Convention on Prior

Informed Consent (PIC)

UNECE Aarhus Protocol on

POPs and Heavy Metals

Not listed.

Not listed.

Not listed.

Product Name: NADREIN Hi-performance Coating Page: 6 / 7 Version 2.01 Date of issue 10/18/2024 Language English

Section 16. Other information

History

Date of issue/Date of revision: 10/18/2024Date of previous issue: 10/18/2019

Version : 2.01

Prepared by : Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from PodLee Company.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The PodLee company shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the PodLee company to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product Name: NADREIN Hi-performance Coating

Version 2.01

Date of issue 10/18/2024

Page: 7 / 7

Language English